

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the application:

LISTING OF CLAIMS:

1. (currently amended): A method for the purification of 1,1-dichloroethane comprising bringing 1,1-dichloroethane containing a compound having a nitro group ~~and/or a hydroxyl group~~ as a stabilizer into contact with zeolite having an average pore size of 3.4 to 11 Å and/or a carbonaceous adsorbent having an average pore size of 3.4 to 11 Å in a liquid phase to reduce the stabilizer.
2. (original): A method for the purification of 1,1-dichloroethane as described in claim 1, wherein an Si/Al ratio of the zeolite is 2 or less.
3. (previously presented): A method for the purification of 1,1-dichloroethane described in claim 1, wherein the zeolite is at least one type selected from a group consisting of Molecular Sieve 4A, Molecular Sieve 5A, Molecular Sieve 10X, and Molecular Sieve 13X.
4. (original): A method for the purification of 1,1-dichloroethane described in claim 1, wherein the carbonaceous adsorbent is Molecular Sieving Carbon 4A and/or Molecular Sieving Carbon 5A.
5. (currently amended): A method for the purification of 1,1-dichloroethane described in claim 1, wherein a temperature for bringing the 1,1-dichloroethane containing the

compound having the nitro group ~~and/or the hydroxyl group~~ as the stabilizer into contact with the zeolite and/or carbonaceous adsorbent is within a range of from -20 to +60°C.

6. (currently amended): A method for the purification of 1,1-dichloroethane described in claim 1, wherein a pressure for bringing the 1,1-dichloroethane containing the compound having the nitro group ~~and/or the hydroxyl group~~ as the stabilizer into contact with the zeolite and/or carbonaceous adsorbent is within a range of from 0 to 1 MPa.

7. (currently amended): A method for the production of 1,1-difluoroethane comprising using as a reaction raw material 1,1-dichloroethane reduced in amount of a compound having a nitro group ~~and/or a hydroxyl group~~ obtained by using the purification method described in claim 1 contained as a stabilizer.

8. (currently amended): A process for the production of 1,1-difluoroethane comprising the following three steps:

(1) a step of using the purification method described in claim 1 to reduce a compound having a nitro group ~~and/or a hydroxyl group~~ contained as a stabilizer in 1,1-dichloroethane;

(2) a step of reacting the 1,1-dichloroethane reduced in amount of the compound having the nitro group ~~and/or the hydroxyl group~~ after the step of (1) with hydrogen fluoride in a gaseous phase in the presence of a fluorination catalyst to obtain a gas mixture mainly containing 1,1-difluoroethane; and

(3) a step of separating the gas mixture mainly containing the 1,1-difluoroethane obtained in the step of (2) and recirculating at least part of an unreacted product to the step (2).

9. (currently amended): A process for the production of 1,1-difluoroethane described in claim 8, wherein the step (2) is conducted by using 1,1-dichloroethane reduced in total content of the compound having the nitro group ~~and/or the hydroxyl group~~ obtained by the step of the above (1) to 30 mass ppm or less.

10. (currently amended): A process for the production of 1,1-difluoroethane described in claim 8, wherein the step (2) is conducted by using 1,1-dichloroethane reduced in total content of the compound having the nitro group ~~and/or the hydroxyl group~~ obtained by the step of the above (1) to 10 mass ppm or less.

11. (currently amended): A process for the production of 1,1-difluoroethane described in claim 7, wherein the compound having the nitro group ~~and/or the hydroxyl group~~ is at least one type of compound selected from a group consisting of nitro methane, nitro ethane, nitro cresol, nitro toluene, and nitro phenol, ~~phenol, cresol, 2,6-di-butyl-p-cresol, and aminomethylphenol.~~

12. (original): A process for the production of 1,1-difluoroethane described in claim 8, wherein the fluorination catalyst used in the step of the above (2) contains at least one type of

element selected from a group consisting of Cu, Mg, Zn, Pb, Cr, Al, In, Bi, Co, and Ni, and the contact temperature is 100 to 350°C.

13. (previously presented): A process for the production of 1,1-difluoroethane described in claim 8, wherein the unreacted product recirculated to the step (2) in the step of the above (3) is at least one type of compound selected from a group consisting of 1-chloro-1-fluoroethane, 1,1-dichloroethane, and hydrogen fluoride.